
Q and S Series with 0x0° style small handle

200, 300, 400 Amp MIG Guns

Issued Jan. 2007 • Index No. SPEC QS234X-1.1

Q400 MIG S-Gun™ shown with OXO® style small curved handle, medium 45° rotating neck and standard trigger.



Long-lasting power cable compression fittings and necks with large tapered gun connections combine to form the foundation of Bernard® Stay-Tite™ technology. This technology ensures optimal conductivity to increase weld consistency and lessen heat output while improving product

durability.

MIG Gun		Description			
	100% NEMA	100%CE	60% CE	35%CE	
Q200	250	200	240	325	CO ₂ Gas
	n/a	175	200	240	80%AR20%CO ₂
Q300 / S300	350	320	370	470	CO ₂ Gas
	n/a	270	310	390	80%AR20%CO ₂
Q400 / S400	400	350	425	520	CO ₂ Gas
	n/a	285	350	440	80%AR20%CO ₂

All Guns are Not Created Equal.

A MIG gun should be durable, easy to use and customized to your specific application. Our MIG guns put you in control: you choose the options you need and we'll build a gun to last. We even ship most of our guns within 24 hours.

Centerfire™ contact tips, nozzles and diffusers are easy-to-use and high performing - they provide better arc starts, less spatter and more consistent welds - and also last up to three times longer than competitive brands.

Necks available in fixed, rotatable and multiple length options for optimal weld accessibility and improved operator comfort. Rotatable necks changeover without tools.

Patented Jump Liner allows quick neck change and replacement of only most commonly worn or clogged liner area, which reduces the amount of time a gun is offline and minimizes inventory.

Liners coiled in-house with proprietary process that improves wire feed performance and 100 percent tested to ensure smoothest wire feed in the industry.

OXO® style handle option allows configuration of Bernard Q-Gun or S-Gun with feel similar to former OXO APX gun.

Back end with durable rigid strain relief and easily interchangeable direct plugs and trigger leads connect to wire feeders and machines from major manufacturers and allow simple maintenance.

Made with Pride and without Compromise in the

Bernard®


An Illinois Tool Works Company 449 West Corning Road, Box 667 Beecher, Illinois 60401 USA Phone: 800-946-2281 (US Only) 708-946-2281 (Outside US)

Fax: 708-946-6726

For more information, visit us at BernardWelds.com



Replacement Parts List



ITEM #	Q200 PART #	Q300 / \$300 Part #	Q400 / S400 PART #	DESCRIPTION	
1	Se	e Centerfire Spec	Nozzle Assy		
2	Se	e Centerfire Spec	Contact Tip		
3	Se	e Centerfire Spec	Gas Diffuser		
4	Se	e Centerfire Spec	Сар		
5		See Neck Spec Sh	Neck		
6	See .	Jump Liner Spec	Jump Liner		
7	4213B	Q300 4213B	Q400 4313B	Stay-Tite™ End Fitting	
		S300 1680046	\$400 1680046		
8	4305	Q300 4305	Q400 1540003	Stay-Tite™ Cone Nut	
		<u>\$300</u> 1540007	<u>\$400</u> 1540008		
NS	4991	Q300 4991	Q400 1520017	Conduit Clamp (2 Req'd)	
		<u>\$300</u> Not Needed	<u>\$400</u> Not Needed		
NS		407709-013	Jacket Clamp (2 Req'd)		
9		1880219	*Handle Kit - Std. Trigger & Locking Trigger		
10		203296-005	Handle Screw, Large (4 Req'd)		
11		2280044	Handle Screw, Small		
12		177272	Handle Nut (4 Reg'd)		
13		2030029	Handle Nut, Small		
14		177488	Trigger, Standard		
		MS2110	Trigger, Locking		
		177379	Trigger, Standard w/Extension		
15		177271	Trigger Pin (2 Req'd)		
16	2520033	Q300 2520033	Q400 2520041	Spring, Strain Relief	
		S300 2520056	S400 2520056		
17			Rigid Strain Relief Kit (Includes Top & Bottom Halves)		
		2520073	Strain Relief with Installed Gas Pin (Bernard Direct Plug)		
	2520069			Strain Relief (Euro Direct Plug)	
		2520066	Strain Relief (All Other Direct Plugs)		
18		4932	Butt Connector (2 Req'd)		
19	See I	Direct Plug Spec S	Direct Plug Components		
20	S	ee Liner Spec She	Liner		
21		1010027	Adapter Block (Not Req'd on Bernard or Euro Direct Plug)		
22		W11127-002	Screw, Strain Relief (Not Req'd on Bernard Direct Plug)		
23	GN2021			Electrical Plug - Non D/S (Not Req'd on Bernard Direct Plug)	
24	1982	Q300 1983Q	Q400 1984Q	[†] Rear Stay-Tite™ Repair Kit	
		<u>S300</u> N/A	S400 N/A		

^{*1880219} Handle Kit includes halves, screws and nuts.

^{†1982, 1983}Q and 1984Q Rear Stay-Tite™ Repair Kit includes, jacket clamp, conduit clamp, cone nut, end fitting, nipple, spacer & butt connectors.

